



## CORRECT POSITIONING

The webbing should pass across bone structure i.e. the lap (hips) and the buckle should lie on or just below the hip.

Anchorage points should be positioned behind the wearer's hips between 30° and 80° below the height of the hips and at least 35cm apart (or 32cm to meet the DETR requirements for UK Buses & Coaches).

## INSTALLATION

The installation of the seat belt, the quality of it's manufacture and it's connection to the vehicle ultimately determine the load that can be absorbed.

Wherever possible anchorages provided by the vehicle manufacturer should be used.

In the event that these are not available a level of restraint can be provided by fabricating anchorage points on the chassis, seat, or sound metal section of the vehicle.

We recommend reinforcing the structure, around the hole created, ensuring there is no serious corrosion, distortion or fracture within 30cm of the anchorage point created. Where the belt is anchored to the seat frame, the frame must be securely attached to the vehicle.


## RAPID BELT (Loop fixing)

Loop belt attachment ends should be prevented from moving in excess of 25mm. This can be achieved by attaching to intersection of frame.

## Regular inspection of the belt & installation is recommended

## IMPORTANT CHECK

- \* Buckle fastens and releases
- \* Webbing is not frayed/damaged
- \* General condition of belt/anchorages



**WARRANTY & DISCLAIMER** - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitting or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.

GSB2220



**WARRANTY & DISCLAIMER** - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitting or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.

GSB2220